

CLAIMS

What is claimed is:

1. A tie-out comprising
a base;
a means for connecting a leash to said base; and
a means for securing said base to a door.
2. A tie-out mountable to a door, the tie-out comprising
a base;
a pressing mechanism adjustably connected with said base; and
at least one ring connected with one of said base and said pressing mechanism.
3. The tie-out of claim 2 wherein said base comprises a first side, a second side, and a third side, wherein said third side forms a bridge between said first side and said second side.
4. The tie-out of claim 3 further comprising a ring hook connected with said first side.
5. The tie-out of claim 4, wherein said at least one ring is connected with said ring hook.
6. The tie-out of claim 3 further comprising a base pad connected with said first side.
7. The tie-out of claim 2, wherein said pressing mechanism comprises
a screw bolt, wherein said screw bolt is threadedly engaged with said base; and
a press platform connected with said screw bolt.
8. The tie-out of claim 7, wherein said at least one ring is connected with said screw bolt.
9. The tie-out of claim 7 further comprising a platform pad connected with said press platform.

10. The tie-out of claim 7 further comprising a threaded nut connected with said base, and wherein said screw bolt is threadedly engaged with said threaded nut.

11. A tie-out mountable to a door, the tie-out comprising
a base defining a U-shape including a first side, a second side, and a third side, wherein said first side and said second side are connected with said third side, and wherein said first side includes a ring hook and said second side includes a screw bolt aperture;
a first ring connected with said ring hook;
a screw bolt defining a first end and a second end, wherein a press platform is connected with said first end and a second ring is connected with said second end; and
wherein said screw bolt is threadedly engaged with said screw bolt aperture.

12. The tie-out of claim 11 further comprising a base pad connected with said first side of said base.

13. The tie-out of claim 11 further comprising a platform pad connected with said press platform.

14. A tie-out mountable to a door, the tie-out comprising
a base including a first side, a second side, and a third side, wherein said third side interconnects said first side and said second;
a first ring connected with said first side of said base;
a bolt threadedly engaged with said second side of said base;
a second ring connected with said bolt; and
a press platform connected with said bolt.

15. The tie-out of claim 14 further comprising a base pad connected with said first side of said base.

16. The tie-out of claim 14 further comprising a platform pad connected with said press platform.

17. The tie-out of claim 14 further comprising a nut connected with said second side of said base, and wherein said bolt is threadedly engaged with said nut.

18. A door-mounted tie-out comprising
a base including a first side, a second side, and a third side, wherein said first side and said second side are connected with said third side, said first side and said second side defining a first distance therebetween;
at least one ring connected with said base; and
a means for adjusting said first distance.

19. The door-mounted tie-out of claim 18 wherein said means for adjusting said first distance comprises a plurality of shims.